

TECHNICAL DATASHEET



TWA/FC 1062 VV/H

PRODUCT FICHE according to European Regulation n° 2016/2281: Information requirements for high temperature process chillers			
Model:	TWA/FC 1062 VV/H		
Type of condensing:	Air-Cooled		
Refrigerant fluid:	R1234ze		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	5.5	[-]
Annual electricity consumption	Q	1478073	kWh/a
Parameters at full load and reference ambient temperature at rating point A (**)			
Rated refrigeration capacity	P _A	1100.94	kW
Rated power input	D _A	360.92	kW
Rated energy efficiency ratio	EER _{DCA}	3.05	[-]
Parameters at rating point B			
Declared refrigeration capacity	P _B	1023.88	kW
Declared power input	D _B	235.92	kW
Declared energy efficiency ratio	EER _{DCB}	4.34	[-]
Parameters at rating point C			
Declared refrigeration capacity	P _C	957.82	kW
Declared power input	D _C	166.87	kW
Declared energy efficiency ratio	EER _{DCC}	5.74	[-]
Parameters at rating point D			
Declared refrigeration capacity	P _D	880.75	kW
Declared power input	D _D	151.59	kW
Declared energy efficiency ratio	EER _{DCD}	5.81	[-]
Other items			
Capacity control		variable	
Degradation co-efficient chillers (*)	C _{dc}	0.90	[-]
GWP of the refrigerant		4.94	kg CO2 eq (100 years)
(**) If C _{dc} is not determined by measurement then the default degradation coefficient of chillers shall be 0.9.			
(**) For staged capacity units, two values divides by a slash ('/') will be declared in each box in the section referring to 'refrigeration capacity' and 'EER'.			