

TECHNICAL DATASHEET



TWA/FC 552 VV/H

PRODUCT FICHE according to European Regulation n° 2016/2281: Information requirements for high temperature process chillers			
Model:	TWA/FC 552 VV/H		
Type of condensing:	Air-Cooled		
Refrigerant fluid:	R1234ze		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	5.63	[-]
Annual electricity consumption	Q	761838	kWh/a
Parameters at full load and reference ambient temperature at rating point A (**)			
Rated refrigeration capacity	P _A	580.87	kW
Rated power input	D _A	184.89	kW
Rated energy efficiency ratio	EER _{DCA}	3.14	[-]
Parameters at rating point B			
Declared refrigeration capacity	P _B	540.21	kW
Declared power input	D _B	120.58	kW
Declared energy efficiency ratio	EER _{DCB}	4.48	[-]
Parameters at rating point C			
Declared refrigeration capacity	P _C	505.36	kW
Declared power input	D _C	85.36	kW
Declared energy efficiency ratio	EER _{DCC}	5.92	[-]
Parameters at rating point D			
Declared refrigeration capacity	P _D	464.69	kW
Declared power input	D _D	79.03	kW
Declared energy efficiency ratio	EER _{DCD}	5.88	[-]
Other items			
Capacity control		variable	
Degradation co-efficient chillers (*)	C _{dc}	0.90	[-]
GWP of the refrigerant		4.94	kg CO2 eq (100 years)
((*) If C _{dc} is not determined by measurement then the default degradation coefficient of chillers shall be 0.9.			
(**) For staged capacity units, two values divides by a slash ('/') will be declared in each box in the section referring to 'refrigeration capacity' and 'EER'.			