

TECHNICAL DATASHEET



TWA/FC 721 TT/H

PRODUCT FICHE according to European Regulation n° 2016/2281: Information requirements for high temperature process chillers			
Model:	TWA/FC 721 TT/H		
Type of condensing:	Air-Cooled		
Refrigerant fluid:	R1234ze		
Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	7.25	[-]
Annual electricity consumption	Q	676645	kWh/a
Parameters at full load and reference ambient temperature at rating point A (**)			
Rated refrigeration capacity	P _A	664.36	kW
Rated power input	D _A	190.73	kW
Rated energy efficiency ratio	EER _{DC,A}	3.48	[-]
Parameters at rating point B			
Declared refrigeration capacity	P _B	617.86	kW
Declared power input	D _B	128.72	kW
Declared energy efficiency ratio	EER _{DC,B}	4.8	[-]
Parameters at rating point C			
Declared refrigeration capacity	P _C	577.99	kW
Declared power input	D _C	75.46	kW
Declared energy efficiency ratio	EER _{DC,C}	7.66	[-]
Parameters at rating point D			
Declared refrigeration capacity	P _D	531.49	kW
Declared power input	D _D	65.53	kW
Declared energy efficiency ratio	EER _{DC,D}	8.11	[-]
Other items			
Capacity control		variable	
Degradation co-efficient chillers (*)	C _{dc}	0.90	[-]
GWP of the refrigerant		4.94	kg CO2 eq (100 years)
(**) If C _{dc} is not determined by measurement then the default degradation coefficient of chillers shall be 0.9.			
(**) For staged capacity units, two values divides by a slash ('/') will be declared in each box in the section referring to 'refrigeration capacity' and 'EER'.			